



MSDS

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT & COMPANY INFORMATION

Manufacturer: Homax Products, Inc./Rhodes American Emergency Phone: 800-255-3924
 468 West Horton Road Information Phone: 800-729-9029
 Bellingham, WA 98226

Product Name: **OOPS! Waterbased Latex Paint Remover**
 Product Number: **710810, 710814**
 Product Description: Latex Paint Remover
 Preparation Date: August 12, 2002
 HMIS Hazard Codes
 Health: 3
 Flammability: 2
 Reactivity: 0
 PP Equipment: B

2. COMPOSITION/INGREDIENTS

Component	%	CAS#	TLV	PEL	Vapor Pressure mmHg@20°C
Dimethyl Succinate	<3%	106-65-0	None	None	
Dimethyl Adipate	<2%	627-93-0	None	None	
Ethyl Alcohol	<9%	64-17-5	1000 ppm	1000 ppm	
Methyl Alcohol	<.5%	67-96-1	200 ppm	200 ppm	
Methyl Isobutyl Ketone	<.1%	108-10-1	100 ppm	100 ppm	
Isopropyl Alcohol	<1 %	67-63-0	400 ppm	400 ppm	
2-Butoxyethanol	<10%	111-76-2	50 ppm	50 ppm	
Anionic Surfactant	<13%	Proprietary	None	None	
Dimethyl Glutarate	<6%	1119-40-0	None	None	
Water	<57%	7732-18-5	None	None	

3. PHYSICAL/CHEMICAL CHARACTERISTICS

Appearance & Odor: Thin colored liquid/solvent with distinctive odor.
 Boiling Range: 100 degrees C
 Melting Point: N/A
 Vapor Pressure (mm Hg/70 F): <.6 mm Hg @ 20 C
 Vapor Density (Air = 1): >1
 Specific Gravity (Water = 1): 1.017-8.39
 Evaporation Rate: <.1 (Butyl Acetate = 1.0)
 Solubility in Water: Complete

4. FIRE & EXPLOSION HAZARD DATA

Flash Point: >200 F Tag closed cup
 Extinguishing Media: Water Fog, foam, dry chemical, carbon dioxide. LEL: N/A UEL: N/A
 Special Fire Fighting Procedure: Do not use direct stream of water on pool fires.
 Protective Equipment: Approved self-contained breathing apparatus & full bunker gear should be worn.
 Unusual Fire & Explosion Hazards: Keep containers cool with water. Pressure build up could result in container rupture. Vapor is heavier than air.

5. REACTIVITY DATA

Stability:	Stable
Conditions To Avoid:	Heat; hot surfaces and all sources of ignition.
Incompatibility (materials to avoid):	Chlorinated compounds and oxidizing materials. Acids, alkalies.
Hazardous Decomposition Products:	Chlorine gas, HCL and other chlorinated compounds, carbon dioxide, carbon monoxide and unidentified organics may be formed during combustion.
Hazardous Polymerization:	Will not occur.
Conditions to Avoid (Poly):	None

6. HEALTH HAZARD DATA

Effects of overexposure

Inhalation: Runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function. May cause blurry vision.

Ingestion: Sore throat, abdominal pain, nausea, vomiting and diarrhea.

Eyes: Irritation including pain, tearing, reddening and swelling.

Skin: Reddening, swelling, rash and redness.

Chronic: May cause injury to kidneys and liver. Loss of memory, intellectual and coordination ability. In extreme cases, unconsciousness and death may occur. Prolonged or repeated over exposure to skin may cause drying, defatting, and dermatitis.

Carcinogenicity: None listed with NTP, IARC or OSHA

Emergency and First Aid Procedures

Inhalation: Remove to area free of vapors and support/restore breathing. Seek medical attention immediately.

Ingestion: **DO NOT INDUCE VOMITING!** If vomiting spontaneously occurs, keep victim's head below the hips to prevent aspiration into lungs. Seek medical attention immediately.

Eyes: Flush with water for at least 15 minutes. Seek medical attention immediately.

Skin: Remove contaminated clothing and wash affected area with soap and water. Do not reuse contaminated articles. Seek medical attention immediately.

7. PRECAUTIONS FOR SAFE HANDLING & USE

Steps if Material Released/Spilled: For large spills, evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak if safe to do so. Dike and contain. If vapor cloud forms, water fog may be used to suppress. Contain run-off. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbant such as clay, sand or other suitable material. Place in non-leaking containers. Seal tightly for proper disposal.

Neutralizing Agent: N/A

Waste Disposal Method: Do not flush into sewers or waterways. Dispose of in accordance with local, county, state and federal regulations.

7. PRECAUTIONS FOR SAFE HANDLING & USE

Precautions-Handling/Storing: Keep product containers cool, dry and away from sources of ignition. Use and store with adequate ventilation in properly labeled, closed containers. Avoid inhalation of vapors and skin contact. DO NOT TAKE

INTERNALLY. Disposal containers must be sealed tightly and properly labeled. Do not eat, drink or smoke in work area.
Wash hands thoroughly after use.
Other Precautions: N/A

8. CONTROL MEASURES

Respiratory Protection: If exposure exceeds TLV, use NIOSH approved respirator.

Ventilation: Use explosion-proof ventilation as required to control vapor concentrations.

Protective Gloves: Chemical resistant

Eye Protection: Splashproof goggles

Other Protective Clothing & Equipment: Safety showers and eye wash stations should be available for use in an emergency.

Work Hygienic Practices: Wash hands thoroughly after use, before drinking, eating or smoking.

Supplier Safety & Health Data: N/A

9. TRANSPORTATION DATA

Hazard Class: Not regulated

UN Number: N/A

NA #: N/A

Other: The ORM-D classification applies to containers under one gallon in size and is not applicable to air shipment.

The information in this document is believed to be correct as of the date issued. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THE PRODUCT, OR THE HAZARDS RELATED TO ITS USE. This information and product are furnished on the condition that the person receiving them shall make his own determination as to the suitability of the product for his particular purpose and on the condition the he assumes the risk of his use thereof.